

MA SERIES PORTABLE PA SYSTEMS



The new **MIPRO MA-808 Portable Wireless PA System** features a rugged, high-impact enclosure with retractable handles and integrated wheels for easy transport. This bi-amplified system delivers clear, powerful sound thanks to a Class AB amplifier for the HF (high frequency) driver and a Class D amplifier that drives a large, 10-inch woofer.

The MA-808 features an optional built-in CD/MP3 player module, support for two optional wireless receiver modules, and storage provisions for the wireless transmitters. The MA-808 is a complete, self-contained PA solution.



MA-808: MIPRO's Premium Portable PA System!

Key Features

- High efficiency Class D, 120-watt RMS amplifier for the 10-inch woofer and a Class AB, 50-watt RMS for the HF driver results in a clear and powerful sound.
- Bi-amplified system has separated high and low frequency amplifiers for enhanced performance.
- High-impact enclosure design with unique luggage-pull design features a functional retractable handle and bottom wheels for effortless transport.
- Hand-carry, table-top or integrated tripod stand mounting capability.
- Simultaneous audio is possible from both wired and wireless microphones as well as the CD/MP3 player.
- Built-in storage compartments for transmitters.
- Up to 2 wireless receiver modules with effortless channel set-up via MIPRO's industry-leading Auto-scan and ACT functions can be installed. Their diversity reception ensures long and reliable transmission free from signal dropouts and interference.
- Universal AC switching power supply ensures constant and reliable voltage worldwide. (the rechargeable battery can be re-charging and used simultaneously)
- High-efficiency output is suitable for large crowds in any event where a portable sound system is required.

MA-808 SPECIFICATIONS

Built-in output power	170W, HF 8 ohms - LF 4 ohms
T.H.D.	Less than 1%
Frequency Response	50Hz - 18kHz (±3dB)
Speaker	HF 1.5" titanium compression driver / LF 10" neodymium cone driver
Active Crossover	2.5 kHz / 12dB octave
Optional Wireless Receiver Modules	Accepts up to 2 MRM-70 16 frequency-agile UHF modules, 620 - 692 MHz
Optional Wireless Microphones	ACT Handheld or bodypack transmitters with lavalier, headworn microphones or instrument adaptors
Optional CD/MP3 Player	Multi-function, anti-shock CD/MP3 player
Audio Inputs	Balanced & unbalanced MIC & LINE
Audio Outputs	RCA unbalanced LINE
Power supply	Two 12V/4a rechargeable batteries & 90-264V AC switching power supply
System Re-charge Time / Operating Time	8 hours to re-charge / up to 6 to 8 hours continuous use
Optional Accessories	SC-80 padded storage/carry bag with accessory pockets; SPS-410 stand; MA-808EXP extension speaker
Dimensions / Weight	14.2" x 13.8" x 22" / 44 lbs
Finish	Black