



The SN-110 is a versatile high efficiency 2-way loudspeaker featuring a 10" low frequency speaker with a 3" voice coil and a 1" exit compression driver with 1.75" titanium diaphragm coupled to a constant directivity horn. The SN-110 is rated at 400 W program power handling. The high frequency driver protection and crossover network enhances efficiency and provides excellent long-term reliability.

The cabinet is a high pressure injection molded high density polypropylene cabinet with a molded handle and stand mounting socket. The internal design provides extensive wall reinforcing for minimum vibration. The SN-110 provides clear, punchy sound and excellent long-term dependability needed in today's stand-alone full-range loudspeaker applications.



SPECIFICATIONS

RMS Power Handling	200 W
Program Power Handling	400 W
On-axis Frequency Range	65-16 KHz
Connectors	Dual paralleled Speakon
Nominal Impedance	8 ohm
On-axis Sensitivity 1W/1m	94 dB SPL
Rated Peak SPL at Full Power	123 dB
Horizontal Coverage (Normal-6dB)	105 deg.
Vertical Coverage (Normal-6dB)	75 deg.
Enclosure Material	High density polypropylene
Color	Black
Dimensions (H x W x D)	20.8 x 13.4 x 12.2 inches
Net Weight	26.4 pounds
Shipping Weight	29.7 pounds

FEATURES

- Two-way vented loudspeaker system.
- 10" low frequency speaker.
- 1.75" compression driver with constant directivity horn.
- 200 W RMS power handling.
- High density polypropylene enclosure.

